



OASIS INTERNATIONAL



UNIVERSAL
BARRIER-FREE VERSACOOLER® II
P8SBFSL, PSBFSL
(P8ACSL, PACSL VersaFiller™ Combination)

Suggested Specification

P8SBFSL shall deliver 8.0 gph of 50° F degree water at 90° F ambient and 80° F inlet water. Model PSBFSL is a nonrefrigerated drinking fountain and delivers ambient water. Both shall include the VersaFiller Sports Bottle Filler with independent manual activation; lower unit must have front and side push pads to activate the manual flow of water for the cooler. VersaFiller alcove and activation button contain Freshield, WHICH UTILIZES a silver-based antimicrobial compound that reduces the growth of micro-organisms and mildew to protect the surfaces from discoloration, odors and degradation. Basin shall be designed to eliminate splashing and standing water. Bubbler shall be a Low Flow, one piece construction with flexible guard and operate between 20 and 120 PSI. VersaFiller cabinet finish is Brushed Stainless Steel. P8ACSL cabinet finish shall be Sandstone Powder Coated paint on galvanized steel or brushed stainless steel. Cooling system shall use R-134a refrigerant. Shall comply with ANSI A117.1 and ADA.

Standard Features

- > Built-in 100 micron strainer stops particles before they enter the waterway
- > Waterways Are Lead-Free In Materials & Construction
- > Stainless Steel Top One Piece, Low Flow, Flexible Bubbler Guard
- > Heavy Duty Galvanized Steel Frame
- > High Efficiency Cooling Tank and Coil
- > Refrigerant R-134a
- > Four Push Pad Manual Activation on water cooler
- > External Stream Height Adjustment cooler
- > Independent Mechanical Activation VersaFiller

Finishes

- > VersaFiller Cabinet Finish is Brushed Stainless Steel
- > Standard Versacooler (bottom unit) Cabinet Finish: Sandstone Powder Coated Paint on Galvanized Steel
- Optional finishes (at additional cost): Brushed Stainless Steel

Installation

- > Prior to roughing consult with local, state, and federal codes for proper mounting height.
- > Shipped with complete instructions and wall mounting brackets.
- > Removable side and front panels provide easy access for installation



VersaFiller alcove is tall enough to accommodate most sizes of refillable water bottles on the market.

Universal split-level: can be installed left high and right low or right high and left low.

Options (at additional cost)

- One piece chrome plated brass bubbler
- Oasis Water Filtration System
- ADA compliant apron

Powder Coated Finish Warranty (Continental limits of the United States and Canada): Three years on the powder coat finish provided that the water cooler has not been subjected to abuse, misuse, or alteration.

Limited 5-Year Warranty (Continental limits of the United States and Canada): Five years on the sealed refrigeration system and most component parts. Detailed warranty certificate enclosed with each water cooler; sample available upon request.

Export Warranty: One year on component parts. Detailed warranty certificate enclosed with each drinking fountain; sample copy available upon request.

Product Certified to NSF/ANSI Standard 61, Annex G (weighted average lead content of <=0.25%) and is in compliance with California's Health & Safety Code Section 116875 (commonly known as AB1953). Models covered by this specification comply with all known Plumbing Codes. Listed by Underwriters' Laboratories to U.S. and Canadian standards.

ADA compliant when properly installed.

For split-level units, optional apron must be installed below upper unit to comply with ADA guidelines.

Components in this fountain are lead free as defined by the Safe Drinking Water Act Amendments of 1986, and the Lead Contamination Control Act of 1988.



Global International Product Certified by NSF to NSF/ANSI Standard 61, G

Model	50° F Drinking Water 90° F Ambient Air Temp*				115 Volts, 60 HZ			Glass Filler Acc. Option	Cabinet Color Finish	Net Wt. Approx.
	Rated Capacity GPH	Base Rate GPH	Pre-Cooler	Hot 'N Cold™ Model	Compr. HP	Full Load Amps	Rated Watts			
P8SBFSL	8.0	8.0	No	No	1/4	4.6	500	No	Yes	94 Lbs.
PSBFSL	Fountain Only							No	Yes	60 Lbs.

* Industry Standard Rating Condition 80° F inlet water temperature.

Specifications subject to change without notice

