

# OASIS<sup>®</sup> Dehumidifiers

## for Professional & Residential Use

Prevent Moisture and Stay Dry with the Oasis  
Portable, Compact, Functional Dehumidifier

**Great for commercial and residential use—Oasis dehumidifiers are the most durable dehumidifiers on the market.** Designed to safeguard people, places and goods from potentially damaging high-humidity conditions, these heavy-duty dehumidifiers extract maximum moisture from the air, providing a drier, healthier, more even-temperature environment.



### Functional Design

Stain resistant, grey-stone, vinyl-on steel laminate with polystyrene grille facilitates free airflow.

### Automatic Humidistat Control

Dial-controlled, adjustable humidistat automatically turns unit on or off at pre-selected moisture levels.

### Frost-Free System

Frost prevention system enables operation in ambient temperatures as low as 43°F.

### Continuous Moisture Removal

Drip tray has threaded fitting for garden hose to funnel into floor drain.

### Concealed Rollers

Simple mobility with three-point suspension system keeps unit level on uneven floors.



CONVENIENT

LONG-LASTING

DEPENDABLE PERFORMANCE

The Oasis Dehumidifier—Technology at work since 1949

Extract maximum moisture from the air for a drier, healthier, more even-temperature environment. Long-lasting and extremely durable, Oasis dehumidifiers provide automatic, hassle-free, high-capacity moisture removal.

## FEATURES

- Sealed Refrigeration Systems plug into standard electrical outlets
- Frost-Free System prevents frost build-up on the evaporator coil in low ambient temperatures
- Automatic Humidistat Control for continuous maximum moisture removal
- Heavy-Duty Vinyl Coated Steel Cabinet protects from stains
- 3-Point Suspension System keeps unit level on uneven floors
- Side Pocket Handles for easy mobility
- Simplified water extraction with Hose-to-Drain Connection
- Automatic Shut-Off Float

## SPECIFICATIONS

Model No.	D-165HG GST
Weight	51.8 lbs
Dimensions	23.8" H x 15" W x 14.3" D
Operating Temperature Range	43° - 109° F
Performance (gallons of water / 24 hours):	
	7.2 Gallons at 86° F, 80% Relative Humidity
	4.4 Gallons at 82° F, 60% Relative Humidity
	2.5 Gallons at 68° F, 60% Relative Humidity
	2.1 Gallons at 50° F, 70% Relative Humidity
Refrigerant	R134a
Refrigerant Charge	.8 lbs
Air Flow	300 cubic feet per minute
Power Consumption	480 watts
Noise	59.8 dB(A)
Defrost System	Hot Gas Valve
Warranty	5 Years
Made in Poland	



800.646.2747 | [oasiscoolers.com](http://oasiscoolers.com)



A WBENC—Certified Women's Business Enterprise

OASIS is a registered trademark of LVD Acquisition, LLC dba Oasis International

© 2011 LVD Acquisition, LLC