



POU Water Coolers

AquaBar™ II Series

(Standard Model)

A sleek and modern POU cooler with features you've come to expect from OASIS®.

Model: POU2LRHK (Hot, Cook, and Cold)

- Modern cabinet design looks great in any home or office.
- 4 gallon stainless steel storage reservoir, perfect for R.O. and filter applications
- High chilling capacity—2 gallons at 50° F per hour. Reliable dual mechanical float
- Large faucet alcove for filling sports bottles and carafes
- Optional Kit for in-tank U.V. for constant sanitization
- Optional in cabinet leak detection with inlet water shut-off
- Optional 8" pedestal to raise unit
- 3-year limited warranty
- Conveniently access safety float reset through cabinet top.



AquaBar™ II Series Technical Data & Specifications



Dimensions:

W 12.75" x D 16.75" x H 44.75"

Net Weight (approx.): 60 lbs.

Cabinet: ABS plastic top and front with removable metal side panels. Holes are pre-drilled on cabinet side for cup dispenser.

Cold Water Refrigeration Unit: Convection cooled condenser. Internally spring mounted, hermetically sealed compressor with automatic overload protector. No lubrication needed. Refrigerant is controlled accurately by a capillary tube.

Cold Water Thermostat: Temperature is controlled by an adjustable thermostat with "Off" position that is easily accessible.

Cold Water Reservoir: 4 gallon non-removable type 300 series stainless steel. External copper refrigerant coil. Encased in pre-fitted molded plastic foam insulation.

Cold Water Capacity: 2.0 gallons of 50°F water per hour (43 x 6 oz cups).

Hot Water Tank: Tank is constructed of type 300 series stainless steel with 500 watt element.

Hot Water Capacity: 45 x 6 oz cups of piping hot water per hour. 1 1/2 quart storage tank.

Hot Water Thermostat: Fixed thermostat with safety limiter.

Hot Water Safety Faucet: Self closing faucet requires a two-step action that is easy for adults to use, but helps to protect small children.

Drip Receptor: Drip tray lifts out for easy removal. Molded for durability, dishwasher safe.

Electrical: 115 volts, 60 Hertz. Water cooler compressor 1/20 hp. Three wire service cord and polarized plug furnished.

Warranty: (Within the Continental Limits of the United States and Canada) Limited three year warranty. Three years on the sealed refrigeration system, with one year on most component parts. Detailed warranty certificate enclosed with each water cooler; sample copy available upon request.

Components in this water cooler are lead free as defined by the Safe Drinking Water Act Amendments of 1986 and the Lead Contamination Control Act of 1988. Model Listed by Underwriter's Laboratories to U.S. and Canadian Standards.

Energy Consumption:

POU2LRHK .678 kwh/day (Energy Savor mode can reduce Energy Consumption by up to 66%).



Specifications are subject to change without notice.

©2009 OASIS International. OASIS® and the palm tree design are registered trademarks of OASIS International. AquaBar™ is a trademark of OASIS International.