



POU Water Coolers

AquaBar™ II Series

A sleek and modern cooler with integral U.V. and built-in leak detection with energy saving features.

- Advanced electronic control center monitors filter and U.V. light life
- 4 gallon stainless steel storage reservoir, perfect for R.O. and filter applications
- In tank U.V. for constant sanitization
- Energy Saver mode
- In cabinet leak detection with inlet water shut-off
- Hot Booster function heats water to optimal temperature for tea
- Front access door for filter installation
- Optional Pedestal raises dispense height by 8 inches (See Photo to the right)
- Energy Star rated
- 3 year limited warranty



AquaBar™ II Series Technical Data & Specifications



Dimensions:

W 12.75" x D 16.75" x H 44.75"

Net Weight (approx.): 60 lbs.

Cabinet: ABS plastic top and front with removable metal side panels. Holes are pre-drilled on cabinet side for cup dispenser.

Cold Water Refrigeration Unit: Convection cooled condenser. Internally spring mounted, hermetically sealed compressor with automatic overload protector. No lubrication needed. Refrigerant is controlled accurately by a capillary tube.

Cold Water Thermostat: Temperature is controlled by an adjustable thermostat with "Off" position that is easily accessible.

Cold Water Reservoir: 4 gallon non-removable type 300 series stainless steel. External copper refrigerant coil. Encased in pre-fitted molded plastic foam insulation.

Cold Water Capacity: 2.0 gallons of 50°F water per hour (43 x 6 oz cups).

Hot Water Tank: Tank is constructed of type 300 series stainless steel with 500 watt element.

Hot Water Capacity: 45 x 6 oz cups of piping hot water per hour. 1 1/2 quart storage tank.

Hot Water Thermostat: Fixed thermostat with safety limiter.

Hot Water Safety Faucet: Self closing faucet requires a two-step action that is easy for adults to use, but helps to protect small children.

Drip Receptor: Drip tray lifts out for easy removal. Molded for durability, dishwasher safe.

Electrical: 115 volts, 60 Hertz. Water cooler compressor 1/20 hp. Three wire service cord and polarized plug furnished.

Warranty: (Within the Continental Limits of the United States and Canada) Limited three year warranty. Three years on the sealed refrigeration system, with one year on most component parts. Detailed warranty certificate enclosed with each water cooler; sample copy available upon request.

Components in this water cooler are lead free as defined by the Safe Drinking Water Act Amendments of 1986 and the Lead Contamination Control Act of 1988. Model Listed by Underwriter's Laboratories to U.S. and Canadian Standards.



Specifications are subject to change without notice.

©2009 OASIS International. OASIS® and the palm tree design are registered trademarks of OASIS International. AquaBar™ is a trademark of OASIS International.