



| Modular Model Comparison Chart | | | | | | | | | |
|--|---|---|--|--|--|---|--|--|--|
| Family | Bi-Level | | Barrier-Free | | Back Panel Fount. | | Split-Level | | Fountain |
| Type | Bi-Level | | Barrier-Free | | Back Panel Fountain | | Split-Level | | Fountain |
| Standard Finish | Stainless Steel | Stainless Steel | Stainless Steel | Stainless Steel | Stainless Steel | Stainless Steel | Stainless Steel | Stainless Steel | Stainless Steel |
| Shape | Square | Square | Square | Square | Square | Square | Square | Square | Square |
| Model | M8SCPM | M8SCEE | M8SBPM | M8SCBEE | M110PM | M140PM | MSSLPM | MSSLEE | F140PM |
| Primary Description | Modular Bi-Level, 8 GPH of Chilled Drinking Water, Stainless, Steel, Push Button Control, ADA Compliant | Modular Bi-Level, 8 GPH of Chilled Drinking Water, Stainless, Steel, Infrared Sensor, ADA Compliant | Modular Barrier-Free, 8 GPH of Chilled Drinking Water, Stainless Steel, Push Button Control, ADA Compliant | Modular Barrier-Free, 8 GPH of Chilled Drinking Water, Stainless Steel, Infrared Sensor, ADA Compliant | Modular Fountain with Back Panel, Non-Refrigerated, Stainless Steel, Push Button Control | Modular Fountain with Back Panel, Non-Refrigerated, Stainless Steel, Push Button Control, ADA Compliant | Modular Split-Level, Non-Refrigerated, Stainless Steel, Push Button Control, ADA Compliant | Modular Split-Level, Non-Refrigerated, Stainless Steel, Infrared Sensor, ADA Compliant | Modular Fountain without Back Panel, Stainless Steel, Non-Refrigerated, Push Button Control, ADA Compliant |
| Capacity | Cold Water (50F /hr) | 8 GPH | 8 GPH | 8 GPH | 8 GPH | N/A | N/A | N/A | N/A |
| Hot Water (6 oz. cups/hr) | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A | N/A |
| Non-Refrigerated | | | | | Y | Y | Y | Y | Y |
| Filtration | Can Add Internally | Y | Y | Y | Y | | | | |
| Split-Level | | Y | Y | | | | Y | Y | |
| Optional Finishes (at additional cost) | Greystone | | | | | | | | |
| Stainless Steel | Y | Y | Y | Y | Y | Y | Y | Y | Y |
| Regency Bronze | Y | Y | Y | Y | Y | Y | Y | Y | Y |
| Other Powder Coat Finishes | | | | | | | | | |
| Controls | Infrared Sensor | | Y | | Y | | | Y | Y |
| Single Push Button Control | Y | | Y | | Y | Y | Y | | |
| Refrigerant | R-134a | Y | Y | Y | Y | | | | |
| Warranty | | 5-Year | 5-Year | 5-Year | 5-Year | 1-Year | 1-Year | 1-Year | 1-Year |
| ADA Compliant | | Y | Y | Y | Y | | Y | Y | Y |
| NSF Certified | | Y | Y | Y | Y | Y | Y | Y | Y |
| Lead-Free | | Y | Y | Y | Y | Y | Y | Y | Y |
| Net Weight | | 154 lbs. | 154 lbs. | 154 lbs. | 154 lbs. | 20 lbs. | 29 lbs. | 59 lbs. | 59 lbs. |
| | | | | | | | | | 13 lbs. |

*gallon per hour ratings are at 50°F chilled water temperature @90°F ambient air temperature and 80°F inlet water temperature.

Specifications Subject to Change Without Notice

©2009 Oasis International
Oasis® is a trademark of Oasis International