



Versacooler® II with Green Filtration System Comparison Chart							
Family	GREEN FILTER						
Type	Green Filtration						
Standard Finish	Sandstone Powder Coat	Sandstone Powder Coat	Sandstone Powder Coat	Sandstone Powder Coat	Sandstone Powder Coat	Sandstone Powder Coat	
Shape	Rectangular	Rectangular	Rectangular	Rectangular	Rectangular	Rectangular	
Model	PF8AC	PF8ACEE	PFAC	PF8ACSL	PF8ACSLEE	PFACSL	
Primary Description	Green Filtration, Barrier-Free, Stainless Steel Top, 8 GPH of Chilled Drinking Water, 4 Push Pad Control	Green Filtration, Barrier-Free, Stainless Steel Top, 8 GPH of Chilled Drinking Water, Infrared Sensor	Green Filtration, Barrier-Free, Stainless Steel Top, Non-Refrigerated, 4 Push Pad Control	Green Filtration, Universal Split-Level, Barrier-Free, Stainless Steel Top, 8 GPH of Chilled Drinking Water, 4 Push Pad Control	Green Filtration, Universal Split-Level, Barrier-Free, Stainless Steel Top, 8 GPH of Chilled Drinking Water, Infrared Sensor	Green Filtration, Universal Split-Level, Barrier-Free, Stainless Steel Top, Non-Refrigerated, 4 Push Pad Control	
Capacity	Cold Water 50F /hr) Hot Water (6oz cups/hr) Non-Refrigerated	8 GPH N/A	8 GPH N/A	N/A Y	8 GPH N/A	8 GPH N/A	N/A Y
Filtration	Can Add Internally Green Filtration System	Y	Y	Y	Y	Y	Y
Universal Split-Level				Y	Y	Y	Y
Optional Finishes (at additional cost)	Greystone Stainless Steel Regency Bronze Other Powder Coat Finishes	Y Y Y Y	Y Y Y Y	Y Y Y Y	Y Y Y Y	Y Y Y Y	Y Y Y Y
Controls	Four Push Pad Control Infrared Sensor Activation Mechanical Push Pad Activation Single Push Button Control	Y	Y	Y	Y	Y	Y
Refrigerant	R-134a	Y	Y		Y	Y	
Warranty		5-Year	5-Year	1-Year	5-Year	5-Year	1-Year
ADA Compliant		Y	Y	Y	Y	Y	Y
Net Weight		59 lbs.	59 lbs.	25 lbs.	84 lbs.	84 lbs.	50 lbs.

*gallon per hour ratings are at 50°F chilled water temperature @90°F ambient air temperature and 80°F inlet water temperature.