



Water Coolers



**VANDAL RESISTANT
UNIVERSAL BARRIER-FREE
VERSACOOLER® II**
Energy and Water Conservation Technology

PGV8ACSL

Suggested Specification

Model PGV8ACSL shall deliver 8.0 gph of 50° F degree water at 90° F ambient and 80° F inlet water. Shall include a single vandal resistant push button to activate the flow of water. Basin shall be designed to eliminate splashing and standing water. Bubbler shall have flexible guard, vandal resistant, and operate between 20 and 120 PSI. Cabinet finish shall be brushed stainless steel. Cabinet shall have perforated galvanized steel screens to prevent objects from being inserted into the cooler. Cooling system shall use R-134a refrigerant. Shall comply with ANSI A117.1 and ADA. Shall be listed by Underwriters' Laboratories to U.S. and Canadian standards. Shall comply with ANSI/NSF 61.

Model

PGV8ACSL Delivers 8.0 gallons of chilled drinking water per hour. This model satisfies CABO/ANSI A117.1 and will comply with ADA guidelines, when properly installed.

Standard Features

- > Built-in 100 micron strainer stops particles before they enter the waterway
- > Waterways are Lead-Free In Materials & Construction
- > Brushed Stainless Steel Finish
- > Stainless Steel Top
- > Vandal Resistant Bubbler With Flexible Guard
- > Heavy Duty Galvanized Steel Frame
- > Galvanized Steel Louver and Bottom Screen
- > High Efficiency Cooling Tank and Coil
- > Refrigerant R-134a
- > Product Certified to NSF/ANSI Standard 61, Annex G (AB1953)
- > Vandal Resistant Front Push Button
- > Vandal Resistant Fasteners
- > Universal models can be installed left high and right low or right high and left low

Finishes

- > Standard Cabinet Finish: Brushed Stainless Steel

Installation

- > Prior to roughing consult with local, state, and federal codes for proper mounting height.
- > Shipped with complete instructions and wall mounting bracket.
- > Removable side and front panels provide easy access for installation.



ADA Compliant when installed in alcove or with right wing wall, or with accessory apron.



Components in this fountain are lead free as defined by the Safe Drinking Water Act Amendments of 1986, and the Lead Contamination Control Act of 1988.

Limited 5-Year Warranty (Continental limits of the United States and Canada): Five years on the sealed refrigeration system and most component parts. Detailed warranty certificate enclosed with each water cooler; sample available upon request.

Export Warranty: One year on the sealed refrigeration system and most component parts. Four-year replacement contract on sealed refrigeration system. Detailed warranty certificate enclosed with each drinking fountain; sample copy available upon request.

Product Certified to NSF/ANSI Standard 61, Annex G (weighted average lead content of $\leq 0.25\%$) and is in compliance with California's Health & Safety Code Section 116875 (commonly known as AB1953).

Models covered by this specification comply with all known Plumbing Codes. Listed by Underwriters' Laboratories to U.S. and Canadian standards.



Certified to NSF/ANSI 61/ Section 9

Model	50° F Drinking Water 90° F Ambient Air Temp*			Hot'N Cold™ Model**	115 Volts, 60 HZ			Glass Filler Acc. Option	Cabinet Color Finish	Net Wt. Approx.
	Rated Capacity GPH	Base Rate GPH	Pre-Cooler		Compr. HP	Full Load Amps	Rated Watts			
PGV8ACSL	8.0	8.0	No	No	1/4	4.4	500	No	No	84 Lbs.

*Industry Standard Rating Condition 80° F inlet water temperature.

Specifications subject to change without notice

