



# Water Coolers



COMPACT ON-A-WALL

## PLF4CM, PCM

### Suggested Specification

Cabinet finish shall be Sandstone powder coat paint on galvanized steel or brushed stainless steel. Cooling system shall use R-134a refrigerant. Shall be listed by Underwriters' Laboratories to U.S. and Canadian standards and conform to European Union Directives. Product Certified to NSF/ANSI Standard 61, Annex G (weighted average lead content of <math>\leq 0.25\%</math>) and is in compliance with California's Health & Safety Code Section 116875 (commonly known as AB1953).

### Models

**PLF4CM** delivers 4.0 gph of chilled drinking water.  
**PCM** is a non-refrigerated fountain.

### Standard Features

- > Waterways are Lead-Free in Materials & Construction
- > Dial-A-Drink® Bubbler
- > Stainless Steel Top
- > Welded Heavy-Gauge Steel Frame
- > High-Efficiency Cooling Tank and Coil
- > Refrigerant R-134a
- > Product Certified to NSF/ANSI Standard 61, Annex G (AB1953)
- > Limited 5-year Warranty

### Finishes

- > Standard Cabinet Finish: Sandstone powder coated paint on Galvanized Steel.
- > Optional finishes at extra cost: Stainless Steel, Powder coated paint.



Components in this fountain are lead free as defined by the Safe Drinking Water Act Amendments of 1986, and the Lead Contamination Control Act of 1988.

### Installation

- > Prior to roughing-in consult with local, state, and federal codes for proper mounting height.
- > Shipped with complete instructions and wall mounting bracket.
- > Removable panels provide easy access for installation.

**Limited 5-Year Warranty** (Continental limits of the United States and Canada): Five years on the sealed refrigeration system and most component parts. Detailed warranty certificate enclosed with each water cooler; sample available upon request.

**Export Warranty:** One year on sealed refrigeration system and most components parts. Four-year replacement contract on sealed refrigeration system. Detailed warranty certificate enclosed with each drinking fountain; sample copy available upon request.

Models covered by this specification complies with all known Plumbing Codes. Listed by Underwriters' Laboratories to U.S. and Canadian standards and conform to European Union Directives.



Certified to NSF/ANSI 61/ Section 9

Model	50° F Drinking Water 90° F Ambient Air Temp*				115 Volts, 60 HZ			Glass Filler Acc. Option	Cabinet Color Finish	Net Wt. Approx.
	Rated Capacity GPH	Base Rate GPH	Pre-Cooler	Hot'N Cold™ Model**	Compr. HP	Full Load Amps	Rated Watts			
PLF4CM**	4.0	2.5	Yes	No	1/8	3.5	400	No	Yes	51 Lbs.
PCM	Fountain Only							No	Yes	24 Lbs.

\*Industry Standard Rating Condition 80° F inlet water temperature.

\*\*Special export models available, operable on 220-240 volts, 50/60 Hz.

Specifications subject to change without notice

OASIS® CPMPACT ON-A-WALL WATER COOLER MODELS PLF3CM, PLF5CM, PCM

