

# Aqua Bar II Deluxe Cooler



## Contemporary Design, Innovative Features & Versatility

### Features:

- ▶ Tri-temp: Hot, Cook and Cold
- ▶ Deluxe model with hot boost, LCD and electronic controls
- ▶ Modern cabinet design accented in satin silver accent trim with marble style panel
- ▶ 4 gallon stainless steel storage reservoir, perfect for reverse osmosis and filter applications
- ▶ High chilling capacity - 43 x 6 oz cups at 50°F per hour
- ▶ Large faucet alcove for filling sports bottles and carafes
- ▶ Optional in-tank UV accessory for continuous sanitization (purchased separately)
- ▶ Optional in-cabinet leak detector accessory with inlet water shut-off (purchased separately)
- ▶ Pre-plumbed for reserve osmosis and filtration systems
- ▶ Dual mechanical float system with back-up safety operates even when the power is out
- ▶ Certified to NSF/ANSI 372 for low lead content
- ▶ Energy star rated
- ▶ UL Listed
- ▶ 3 year limited warranty



### Model:

- ▶ Deluxe Tri-temp: POC2LRHK



# Aqua Bar II Deluxe Specifications

**Cabinet:** Modern cabinet design accented in satin silver accent trim with marble style panel. Sleek injection molded ABS plastic top and front with powder coat finished removable metal side panels. Pre-drilled holes on cabinet side for simple cup dispenser installation.

**Water Dispensing System:** Easy to use buttons located on front display panel for tri-temp dispensing of hot, cold and room temperature water. Large faucet alcove for filling reusable containers.

**Cold Water Refrigeration Unit:** Convection cooled condenser. Internal, spring mounted, hermetically sealed compressor with automatic overload protector requires no lubrication. Refrigerant is controlled by a capillary tube.

**Hot and Cold Water Thermostat:** Temperature is controlled by a digital display on front of unit with energy saver mode.

**Cold Water Reservoir:** Four gallon, Non-removable type 300 series stainless steel with external copper refrigerant coil. Encased in pre-fitted molded plastic foam insulation.

**Cold Water Capacity:** 2.0 gallons of 50°F water per hour (43 x 6oz cups).

**Hot Water Tank:** Tank is constructed of type 300 series stainless steel with 450 watt element.

**Hot Water Capacity:** 45 x 6 oz. cups of piping hot water per hour. 1 1/2 quart storage tank.

**Hot Water Safety Faucet:** Self-closing activation requires a two-step action to prevent accidental dispensing.

Dimensions: W 12 3/4" x D 16 3/4" x H 44 3/4"  
Approximate Net Weight: 60 lbs.

**Drip receptor:** Durable dishwasher safe drip tray lifts out for easy cleaning.

**Electrical:** 115 volts, 60 hertz. 1/20 hp water cooler compressor. Three wire service cord & polarized plug.

**Optional water Filtration and Reverser Osmosis (RO):** Aqua Bar II deluxe is filter and RO ready and is available with the Oasis three stage green filter system with RO.

**Lead-Free:** Components in the water cooler are lead-free as defined by the Safe Drinking Water Act Amendments of 1986 and the Lead Contamination Control Act of 1988. Model listed by Underwriter's Laboratories to U.S. and Canadian Standards.

**Warranty:** Limited 3-year warranty (within the Continental Limits of the U.S. and Canada). Three years on the sealed refrigeration system, one year on most component parts. Detailed warranty certificate enclosed with each cooler; sample copy available upon request.

Specifications are subject to change without notice



# Aqua Bar II Standard Cooler



Contemporary Design, Innovative Features & Versatility

## Features:

- ▶ Tri-temp: Hot, Cook and Cold
- ▶ 4 gallon stainless steel storage reservoir, perfect for reverse osmosis and filter applications
- ▶ High chilling capacity - 43 x 6 oz cups at 50°F per hour
- ▶ Large faucet alcove for filling sports bottles and carafes
- ▶ Optional in-tank UV accessory for continuous sanitization (purchased separately)
- ▶ Optional in-cabinet leak detector accessory with inlet water shut-off (purchased separately)
- ▶ Dual mechanical float system with back-up safety operates even when the power is out
- ▶ Certified to NSF/ANSI 372 for low lead content
- ▶ Energy star rated
- ▶ UL Listed
- ▶ 3 year limited warranty



## Model:

- ▶ Standard Tri-temp: POU2LRHK



# Aqua Bar II Standard Specifications

**Cabinet:** ABS plastic front and top with powder coat finished removable metal side panels. Holes are pre-drilled on cabinet side for cup dispenser.

**Cold Water Refrigeration Unit:** Convection cooled condenser. Internal, spring mounted, hermetically sealed compressor with automatic overload protector requires no lubrication. Refrigerant is controlled by a capillary tube.

**Cold Water Thermostat:** Temperature is controlled by an adjustable thermostat with "off" position that is easily accessible

**Cold Water Reservoir:** Four gallon, Non-removable type 300 series stainless steel with external copper refrigerant coil. Encased in pre-fitted molded plastic foam insulation.

**Cold Water Capacity:** 2.0 gallons of 50°F water per hour (43 x 6oz cups).

**Hot Water Tank:** Tank is constructed of type 300 series stainless steel with 500 watt element.

**Hot Water Capacity:** 45 x 6 oz. cups of piping hot water per hour. 1 1/2 quart storage tank.

**Hot Water Thermostat:** Fixed thermostat with safety limiter.

**Hot Water Safety Faucet:** Self-closing activation requires a two-step action to prevent accidental dispensing.

**Drip receptor:** Durable dishwasher safe drip tray lifts out for easy cleaning.

**Electrical:** 115 volts, 60 hertz. 1/20 hp water cooler compressor. Three wire service cord & polarized plug.

Dimensions: W 12 3/4" x D 16 3/4" x H 44 3/4"  
Approximate Net Weight: 60 lbs.

## Optional water Filtration and Reverser

**Osmosis (RO):** Aqua Bar II deluxe is filter and RO ready and is available with the Oasis three stage green filter system with RO.

**Lead-Free:** Components in the water cooler are lead-free as defined by the Safe Drinking Water Act Amendments of 1986 and the Lead Contamination Control Act of 1988. Model listed by Underwriter's Laboratories to U.S. and Canadian Standards.

**Warranty:** Limited 3-year warranty (within the Continental Limits of the U.S. and Canada). Three years on the sealed refrigeration system, one year on most component parts. Detailed warranty certificate enclosed with each cooler; sample copy available upon request.

Specifications are subject to change without notice

