



PLF8SY
Manual, Refrigerated
Drinking Fountain

PLF8SY is the ideal slim surface-mount drinking fountain solution for those compact spaces!

PLF8SY delivers 60LPH of 10°C water at 21°C ambient. This semi-recessed drinking fountain is manually activated via the Dial-A-Drink adjustable bubbler.

Complies with ANSI A117.1 and ADA. Shall comply with all relevant CE directives (LVD , EMC, RoHS). Shall comply with ANSI/NSF 61.

Suitable for public building, gymnasiums, sports complexes, hospitals, schools, and offices.

The cooling system uses R-134a or R-290a refrigerant.



MODEL CODE	PLF8SY
ACTIVATION	Mechanical (Dial-A-Drink Adjustable Bubbler with Flexible Bubbler Guard)
FILTRATION	Green Filter (optional), Built-in 100 micron strainer
DISINFECTION	Ultra Blu V (optional)
AUTO-OFF WATER FLOW	No
DRAINAGE TYPE	Built in drain
EXTERIOR	Brushed Stainless Steel
CHASSIS	Heavy Duty Galvanised Steel
BACKSPLASH HEIGHT	48 mm
DIMENSIONS	1140(H) x 440(W) x 241(D) mm (114 recessed)
NET WEIGHT	32 kg
POWER SUPPLY	220-240V, 50/60 Hz
COOLING PERFORMANCE	60 LPH Rated Capacity & Base Rate (10°C in 21°C amb. temp.)
FULL LOAD AMPS	2.2A
RATED WATTS	340 W
ENERGY SYSTEM	Refrigeration is on only when in use or if water temp increases during long period of standby.
COUNTRY OF ORIGIN	Mexico
CERTIFICATIONS	ANSI/NSF 61, CABO/ANSI A117.1, ADA, CE (LVD, EMC, RoHS)
WARRANTY	1 Year

