

M12SBFY Manual, Refrigerated M8SBFY Manual, Refrigerated MSBF Manual, Non-Refrigerated Hydration Station Combo

M12SBFY

Delivering 90LPH of 10°C water at 21°C ambient. Cooling system uses R-134a refrigerant.

M8SBFY

Delivering 60LPH of 10°C water at 21°C ambient. Cooling system uses R-134a refrigerant.

MSBF

Delivering ambient drinking water.

This surface mount hydration station combos is manually activated. The bottle filler requires a push of the touch-button, while the drinking fountain is activated via the push-button.

Key moulded components shall contain Freshield, which utilises a silver-based antimicrobial compound that reduces the growth of microorganisms and mildew to protect the surfaces from discolouration, odours and degradation.

Suitable for public building, gymnasiums, sports complexes, hospitals, schools, and offices.



— MODEL CODE —	M12SBFY —	M8SBFY —	— MSBF —
ACTIVATION	Bottle Filler: Manual (Touch-button) Drinking Fountain: Manual (Push-button)		
FILTRATION	Green Filter (optional), Built-in 100 micron strainer		
AUTO-OFF WATER FLOW	No		
DRAINAGE TYPE	Built in drain, Removable drip tray		
EXTERIOR	Antimicrobial ABS Plastic, Brushed Stainless Steel		
CHASSIS	Heavy Duty Galvanised Steel		
DIMENSIONS	1035(H) x 1003(W) x 483(D) (287 recessed)		
ALCOVE HEIGHT	265 mm		
NET WEIGHT	73 kg		49 kg
POWER SUPPLY	220-240V, 50/60 Hz		-
COOLING PERFORMANCE	90 LPH Rated Capacity & Base Rate (10°C in 21°C amb. temp.)	60 LPH Rated Capacity & Base Rate (10°C in 21°C amb. temp.)	Non-Refrigerated
FULL LOAD AMPS	3.7A	2.2A	-
RATED WATTS	620 W	340 W	-
ENERGY SYSTEM	Refrigeration is on only when in use or if water temp increases during long period of standby.		-
COUNTRY OF ORIGIN	Mexico		
CERTIFICATIONS	ANSI/NSF 61, CABO/ANSI A117.1, ADA, CE (LVD, EMC, RoHS), WRAS		
WARRANTY	1 Year		







