



M12WRSBFY ■ Manual, Refrigerated
M8WRSBFY ■ Manual, Refrigerated
 Hydration Station Combo

M12WRSBFY

Delivering 90LPH of 10°C water at 21°C ambient.
 Cooling system uses R-134a refrigerant.

M8WRSBFY

Delivering 60LPH of 10°C water at 21°C ambient.
 Cooling system uses R-134a refrigerant.



This surface mount hydration station combo is manually activated. The bottle filler requires a push of the touch-button, while the drinking fountains are activated via the push-buttons.

Key moulded components shall contain Freshield, which utilises a silver-based antimicrobial compound that reduces the growth of micro-organisms and mildew to protect the surfaces from discolouration, odours and degradation.

Suitable for public building, gymnasiums, sports complexes, hospitals, schools, and offices.

MODEL CODE	M12WRSBFY	M8WRSBFY
ACTIVATION	Bottle Filler: Contactless (Infrared sensor) Drinking Fountain: Manual (Push-button)	
SENSOR COVERAGE	Up to 5cm (approx.)	
FILTRATION	Green Filter (optional), Built-in 100 micron strainer	
AUTO-OFF WATER FLOW	Bottle Filler: Yes ; Drinking Fountain: No	
DRAINAGE TYPE	Built in drain, Removable drip tray	
EXTERIOR CHASSIS	Antimicrobial ABS Plastic, Brushed Stainless Steel	
DIMENSIONS	Heavy Duty Galvanised Steel	
ALCOVE HEIGHT	1143(H) x 502(W) x 483(D) (287 recessed)	
NET WEIGHT	265 mm	
POWER SUPPLY	73 kg	
COOLING PERFORMANCE	220-240V, 50/60 Hz	
FULL LOAD AMPS	90 LPH Rated Capacity & Base Rate (10°C in 21°C amb. temp.)	60 LPH Rated Capacity & Base Rate (10°C in 21°C amb. temp.)
RATED WATTS	3.7A	2.2 A
ENERGY SYSTEM	620 W	340 W
COUNTRY OF ORIGIN	Refrigeration is on only when in use or if water temp increases during long period of standby.	
CERTIFICATIONS	Mexico	
WARRANTY	ANSI/NSF 61, CABO/ANSI A117.1, ADA, CE (LVD, EMC, RoHS) , WRAS	
	1 Year	

