



**VERSACOOLER PV8ACY** ■ Manual, Refrigerated, Vandal-Resistant  
**VERSACOOLER PVAC** ■ Manual, Non-Refrigerated, Vandal-Resistant  
 Drinking Fountain

**VersaCooler PV8ACY**

Delivering 60LPH of 10°C water at 21°C ambient.  
 Cooling system uses R-134a refrigerant.

**VersaCooler PVAC**

Delivering ambient drinking water.



These surface mount drinking fountains are manually activated via the vandal-resistant touch-button.

Key Versacooler moulded components shall contain Freshield, which utilises a silver-based antimicrobial compound that reduces the growth of micro-organisms and mildew to protect the surfaces from discolouration, odours and degradation.

Complies with ANSI A117.1 and ADA. Shall comply with all relevant CE directives (LVD , EMC, RoHS). Shall comply with ANSI/NSF 61.

Suitable for public building, gymnasiums, sports complexes, hospitals, schools, and offices.

MODEL CODE	PV8ACY	PVAC
ACTIVATION	Mechanical (Vandal-Resistant touch-button)	
FILTRATION	Green Filter (optional), Built-in 100 micron strainer	
DISINFECTION	Ultra Blu V (optional)	
AUTO-OFF WATER FLOW	No	
DRAINAGE TYPE	Built in drain	
EXTERIOR CHASSIS DIMENSIONS	Antimicrobial ABS Plastic, Brushed Stainless Steel Heavy Duty Galvanised Steel 480(H) x 448(W) x 473(D) mm	
NET WEIGHT	27 kg	11 kg
POWER SUPPLY	220-240V, 50/60 Hz	
COOLING PERFORMANCE	60 LPH Rated Capacity & Base Rate (10°C in 21°C amb. temp.)	Non-Refrigerated
FULL LOAD AMPS	2.2A	-
RATED WATTS	450 W	-
ENERGY SYSTEM	Refrigeration is on only when in use or if water temp increases during long period of standby.	
COUNTRY OF ORIGIN	Mexico	
CERTIFICATIONS	ANSI/NSF 61, CABO/ANSI A117.1, ADA, CE (LVD, EMC, RoHS)	
WARRANTY	1 Year	

