



## QUASAR PEBQY ■ Contactless + Manual, Non-Refrigerated Hydration Station Combo

This surface mount hydration station combo has two activation methods. The bottle filler includes an electronic sensor for a contactless (touch free) activation and a 30 second shut off timer. The drinking fountain is activated via one of four push-pads.

The Bottle Counter conveniently displays the number of times the unit has been used, encouraging the refill of sports bottles. Quasar bottle fillers shall have UVC-LED treatment at the point of dispense, which disinfects the water while it is being dispensed; Killing 99.99% of bacteria. UVC-LED also cycles on periodically to keep the dispense-point sanitized between dispenses.

Quasar bottle fillers shall have UVC-LED treatment at the point of dispense, which disinfects the water while it is being dispensed; Killing 99.99% of bacteria. UVC-LED also cycles on periodically to keep the dispense-point sanitized between dispenses.

Key Quasar bottle filler moulded components shall contain Freshield, which utilises a silver-based antimicrobial compound that reduces the growth of micro-organisms and mildew to protect the surfaces from discolouration, odours and degradation.

Suitable for public building, gymnasiums, sports complexes, hospitals, schools, and offices.



| MODEL CODE          | PEBQY 507053   |
|---------------------|--|
| ACTIVATION          | Bottle Filler: Contactless (Infrared sensor)<br>Drinking Fountain: Manual (Four push-pads) |
| SENSOR COVERAGE     | Up to 5cm (approx.)  |
| FILTRATION          | Green Filter (optional), Built-in 100 micron strainer                                      |
| DISINFECTION        | Quasar UVC-LED   |
| AUTO-OFF WATER FLOW | Bottle Filler: Yes ; Drinking Fountain: No   |
| DRAINAGE TYPE       | Built in drain, Removable drip tray  |
| EXTERIOR            | Antimicrobial ABS Plastic, Brushed Stainless Steel   |
| CHASSIS             | Heavy Duty Galvanised Steel  |
| DIMENSIONS          | 960(H) x 413(W) x 473(D)   |
| ALCOVE HEIGHT       | 292 mm   |
| NET WEIGHT          | 16 kg  |
| POWER SUPPLY        | 220-240V, 50/60 Hz   |
| COOLING PERFORMANCE | -  |
| FULL LOAD AMPS      | 0.1A   |
| RATED WATTS         | 7 W  |
| ENERGY SYSTEM       | -  |
| COUNTRY OF ORIGIN   | Mexico   |
| CERTIFICATIONS      | ANSI/NSF 61, CABO/ANSI A117.1, ADA, CE (LVD, EMC, RoHS), WRAS                              |
| WARRANTY            | 1 Year   |

