

OASIS[®]

OASIS INTERNATIONAL

AQUA POINTE[™]

UNIVERSAL BI-LEVEL MODULAR WITH
SPORTS BOTTLE FILLER

Universal Installation



M8CRSBF

Suggested Specification

Model M8CRSBF Shall deliver 8gph of 50°F water at 90°F ambient and 80°F inlet water to a bi level modular fountain with vadal resistant mechanical push button and a low flow one piece bubbler with flexible guard. Water flow to the bottle filler is dispensed through a mechanically activated push button. Key AquaPointe bottle filler component contain FRESHSHIELD which utilizes a silver-based antimicrobial compound that reduces the growth of micro-organisms and mildew to protect the surfaces from discoloration, odors and degradation. Basin shall be designed to eiminate splashing and standing water. Cooling system shall use R-134a refrigerant. Shall comply with ANSI A117.1 and ADA.

Model

M8CRSBF delivers 8.0 gph of chilled drinking water.

Standard Features

- Built-in 100 micron strainer stops particles before they enter the waterway
- Waterways are Lead-free in materials and construction
- Heavy duty steel frame
- Flexible one piece water saver bubbler guard
- High efficiency cooling tank and coil
- Refrigerant R-134a
- Built in panel locks for easy access to chiller and filtration

Installation

- Prior to roughing, consult with local, state and federal codes for proper mounting height
- Shipped with complete instructions and wall mounting bracket
- Removable front panels allow for easy access to filtration and refrigeration unit
- Does not require a recessed mounting frame, but water supply, electrical and waste drain required.

Options (at additional cost)

- One Piece Chrome Plated Brass Bubblers
- 12 gph Chiller (M12CRSBF)
- Oasis Green Filter System

Finishes

Standard cabinet finish: Brushed Stainless Steel

Components in this fountain are lead free as defined by the Safe Drinking Water Act Amendments of 1986, and the Lead Contamination Control Act of 1988.

ADA compliant for reach ranges. These models meet guidelines for children's (ages 5 and up) accessibility providing the floor to button height is less than 40 inches and proper clear floor space is provided for frontal approach. Fountain is ADA compliant for Adults in Wheelchairs.

Product certified to NSF/ANSI standard 61, Annex G (weighted average lead content of <=0.25%) and is in compliance with California's health and safety code section 116875 (commonly known as AB1953). The green filter has been tested to ANSI/NSF standards 42 not by NSF.

Models covered by this specification comply with all known plumbing codes. Listed by Underwriters' Laboratories to U.S. and Canadian standards.



Freshield



Certified to NSF/ANSI 61-2018

Model	50° F Drinking Water 90° F Ambient Air Temp*		115 Volts, 60 HZ			Cabinet Color Finish	Net Wt. Approx.
	Rated Capacity GPH	Base Rate GPH	Compr. HP	Full Load Amps	Rated Watts		
M8CRSBF	8.0	8.0	1/4	4.8	550	NO	180 Lbs.

*Industry Standard Rating Condition 80°F inlet water temperature.

Specifications subject to change without notice

[illegible]

- | THIRD ANGLE PROJECTION | ROUGHING-IN AND DIMENSIONAL DRAWING |
|---|---|
|  |  |