



AQUA BAR II STANDARD COOLER

Model Code:

- Standard Tri-temp - POU2LRHK

Features:

- Tri-temp: Hot, Cold, and Room temperature dispensing
- 4 gallon stainless steel storage reservoir, perfect for reverse osmosis applications where room for external ballast tank is limited
- Removable front access panel with room for filter installation
- High chilling capacity - 43 x 6 oz cups at 50°F per hour, ideal for large offices
- Large faucet alcove for filling sports bottles and carafes
- Handles on sides for easy transport and placement
- Adjustable feet for leveling
- Optional in-tank UV accessory for continuous sanitization (purchased separately)
- Optional in-cabinet leak detector accessory with inlet water shut off (purchased separately)
- Dual electrical float system with back-up safety
- Certified to NSF/ANSI 372 for low lead content
- Energy Star certified
- UL Listed
- 3 year limited warranty



Cabinet:

ABS plastic front and top with powder coat finished removable metal side panels. Holes are predrilled on cabinet side for cup dispenser.

Cold Water Refrigeration Unit:

Convection cooled condenser. Internal, spring mounted, hermetically sealed compressor with automatic overload protector requires no lubrication. Refrigerant is controlled by a capillary tube.

Cold Water Thermostat:

Temperature is controlled by an adjustable thermostat with "off" position that is easily accessible

Cold Water Reservoir:

Four gallon, non-removable type 300 series stainless steel with external copper refrigerant coil. Encased in pre-fitted molded plastic foam insulation.

Hot Water Tank:

Tank is constructed of type 300 series stainless steel with 450 watt element.

Hot Water Capacity:

45 x 6 oz. cups of piping hot water per hour. 1 1/2 quart storage tank.

Hot Water Thermostat:

Fixed thermostat with safety limiter.

Hot Water Safety Faucet:

Self-closing activation requires a two-step action that's easy for adults to use, but protects small children.

Drip Receptor:

Durable dishwasher safe drip tray lifts out for easy cleaning.

Electrical:

115 volts, 60 hertz. 1/20 hp water cooler compressor. Three wire service cord & polarized plug.

Optional Water Filtration and Reverse Osmosis (RO):

Aqua Bar II deluxe is filter and RO ready and is available with the OASIS three stage green filter system with RO.

Certifications:

Product certified to meet lead-free requirements as defined by California, Vermont, and Maryland state laws and the U.S. Safe Drinking Water Act. Model listed by Underwriters laboratories to U.S. and Canadian Standards. Energy Star Certified.

Warranty:

Limited 3-year warranty (within the Continental Limits of the U.S. and Canada). Three years on the sealed refrigeration system, one year on most component parts. Detailed warranty certificate enclosed with each cooler; sample copy available upon request.

Specifications are subject to change without notice



WARNING:
Cancer and Reproductive Harm
www.P65Warnings.ca.gov

DIMENSIONS

	DEPTH	WIDTH	HEIGHT	WEIGHT
POU2LRHK PRODUCT	17.7"	13.2"	45.4"	61.2 lbs
PACKAGING	18.7"	15.2"	47.7"	66.2 lbs

COLD WATER CAPACITY

ROOM TEMP	WATER TEMP	GALLONS PER HOUR AT 50°F	NUMBER OF 3 OZ. CUPS PER HOUR
70°F	70°F	2.4	102
80°F	80°F	1.7	72
90°F	90°F	1.0	42
100°F	100°F	0.7	29

OASIS INTERNATIONAL

www.oasiscoolers.com

222 East Campus View Blvd.
Columbus, OH 43235

1-800-646-2747