



We Know Water.

CONTACTLESS VERSACOOLER® II WITH CONTACTLESS VERSAFILLER® WITH VERSAFILTER™ III

• PG8FEBFT • PGFEBFT

Suggested Specification

Model PG8FEBFT shall deliver 8.0 gph of 50°F water at 90°F ambient and 80°F inlet water per ASHRAE 18 testing. Model PGFEBFT a non-refrigerated model and delivers ambient drinking water. Shall include the VersaFiller® with contactless activation and laminar flow; lower unit shall have infrared sensor to activate the flow of water for the cooler. Bottle Filler alcove and cabinet finish shall be stainless steel. Key VersaFiller components contain Freshield®, which utilizes a silver-based antimicrobial compound to protect the surfaces from discoloration, odors and degradation caused by the growth of micro-organisms and mildew. Basin shall be designed to eliminate splashing and standing water. Water saver bubbler to reduce waste water by 50% and shall have flexible guard and operate between 20 and 100 PSI. Shall use R-134a refrigerant. Shall comply with ANSI 117.1 and ADA. Shall be listed by Underwriters Laboratories to US and Canadian standards, and comply with NSF/ANSI 61 and NSF/ANSI 372.

	PG8FEBFT	PGFEBFT
Features:	<ul style="list-style-type: none">Built-in 100 micron strainer stops particles before they enter the waterwayWaterways are lead-free in materials & constructionHigh efficiency cooling systemStainless steel top and heavy duty galvanized steel frameContactless activation bottle filler with programmable auto shut offFlexible one-piece water saver bubbler infused with silver-based antimicrobial additiveIncludes integral self-scouring waste drainExternal access to stream height adjustment on lower Versacooler fountainExternal access to thermostat with tool activated OFF positionVersaFilter III located in top bottle filler for easy filter replacement with Tilt 'N TetherBuilt-in filter monitor and bottle counterLogos permanently formed into the alcove and stainless steel wrapperLED lighted alcove	
Filtration:	VersaFilter III is Certified to NSF/ANSI 42 and 53 for lead, cyst, Particulate Class I, chlorine, taste and odor reduction to 4,750 gallons	
Power:	115 Volts, 60 Hz	
Activation By:	Contactless Sensor on Bottle Filler and Fountain	
Mounting Type:	Wall Mounted	
Chilling Option:	8.0 gph*	Non-refrigerated
Full Load Amps:	5.0 amps	0.2 amps
Rated Watts:	500	11
Approx. Net Weight:	64 lbs	33 lbs
Installation Location:	Indoor	



Installation

- Prior to rough-in consult with local, state and federal codes for proper mounting height
- Shipped with complete instructions and wall mounting bracket
- Removable side and front panels provide easy access for installation.

Finishes

- Standard: Greystone powder coat on galvanized steel
- Sandstone powder coat on galvanized steel; stainless steel (at additional cost)

Options

- One piece chrome plated brass bubbler (036700-001)

Limited 5-Year Warranty

(Continental limits of the United States and Canada)
Five years on the sealed refrigeration system and most component parts. Detailed warranty certificate enclosed with each water cooler; sample available upon request.

Export Warranty

One year on components parts. Detailed warranty certificate enclosed with each drinking fountain; sample copy available upon request.

Certifications/Compliance

- Certified to UL 399 and CAN/CSA C22.2 No.120 (electric water coolers only)
- Product Certified to NSF/ANSI Standard 61-G & 372 and conforms with the lead content requirements for "Lead Free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act
- These water coolers comply with the requirements of ADA (Americans with Disabilities Act) when properly installed



WARNING:
Cancer and Reproductive Harm
www.P65Warnings.ca.gov



*Industry standard rating condition at 90°F ambient, 80°F inlet water and 50°F drinking water temperature

Specifications subject to change without notice

OASIS CONTACTLESS VERSACOOLER® II WITH CONTACTLESS VERSAFILLER® WITH VERSAFILTER™ III

