



We Know Water.

**BARRIER-FREE VERSACOOLER® II WITH
VERSAFILLER® WITH VERSAFILTER™ III**

- **PG8FSBF**
- **PGFSBF**

Suggested Specification

Model PG8FSBF shall deliver 8.0 gph of 50°F water at 90°F ambient and 80°F inlet water per ASHRAE 18 testing. Model PGFSBF is a non-refrigerated model and delivers ambient drinking water. Shall include the VersaFiller® Sports Bottle Filler with independent manual activation and laminar flow; lower unit shall have four push pads to activate the manual flow of water for the cooler. Key VersaFiller components contain Freshield®, which utilizes a silver-based antimicrobial compound to protect the surfaces from discoloration, odors and degradation caused by the growth of micro-organisms and mildew. Basin shall be designed to eliminate splashing and standing water. Water saver bubbler to reduce waste water by 50% and shall have flexible guard and operate between 20 and 100 PSI. Shall use R-134a refrigerant. Shall comply with ANSI 117.1 and ADA. Shall be listed by Underwriters Laboratories to US and Canadian standards, and comply with NSF/ANSI 61 and NSF/ANSI 372.



	PG8FSBF	PGFSBF
Features:	<ul style="list-style-type: none"> • Built-in 100 micron strainer stops particles before they enter the waterway • Waterways are lead-free in materials & construction • Flexible one-piece water saver bubbler infused with silver-based antimicrobial additive • Stainless steel top and heavy duty galvanized steel frame • Independent manual activation on VersaFiller bottle filler • VersaFilter III located in top bottle filler for easy filter replacement with Tilt 'N Tether • Includes integral self-scouring waste drain • External access to stream height adjustment on lower Versacooler fountain • External access to thermostat with tool activated OFF position 	
Filtration:	VersaFilter III is Certified to NSF/ANSI 42 and 53 for lead, Particulate Class I, chlorine, taste and odor reduction to 4,750 gallons	
Power:	115 Volts, 60 Hz	
Activation By:	Independent Manual Activation on Bottle Filler and Fountain	
Mounting Type:	Wall Mounted	
Chilling Option:	8.0 gph*	Non-refrigerated
Full Load Amps:	5.0 amps	0 amps
Rated Watts:	500	0
Approx. Net Weight:	60	29
Installation Location:	Indoor	

Installation

- Prior to rough-in consult with local, state and federal codes for proper mounting height
- Shipped with complete instructions and wall mounting bracket
- Removable side and front panels provide easy access for installation.

Finishes

- Standard: Greystone powder coat on galvanized steel
- Sandstone powder coat on galvanized steel; stainless steel (at additional cost)

Options

- One piece chrome plated brass bubbler (036700-001)

Limited 5-Year Warranty

(Continental limits of the United States and Canada) Five years on the sealed refrigeration system and most component parts. Detailed warranty certificate enclosed with each water cooler; sample available upon request.

Export Warranty

One year on components parts. Detailed warranty certificate enclosed with each drinking fountain; sample copy available upon request.

Certifications/Compliance

- Certified to UL 399 and CAN/CSA C22.2 No.120 (electric water coolers only)
- Product Certified to NSF/ANSI Standard 61-G & 372 and conforms with the lead content requirements for "Lead Free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act
- These water coolers comply with the requirements of ADA (Americans with Disabilities Act) when properly installed

WARNING:
Cancer and Reproductive Harm
www.P65Warnings.ca.gov

*Industry standard rating condition at 90°F ambient, 80°F inlet water and 50°F drinking water temperature



Specifications subject to change without notice

OASIS VERSACOOLER® II WITH VERSAFILLER® WITH VERSAFILTER™ III

