



**We Know Water.**

## UNIVERSAL BI-LEVEL VERSACOOLER® II FILTERED

- **PGF8ACSL**
- **PGFACSL**

### Suggested Specification

Model PGF8ACSL shall deliver 8.0 gph of 50°F water at 90°F ambient and 80°F inlet water per ASHRAE 18 testing. Model PGFACSL is a non-refrigerated drinking fountain and delivers ambient water. Each fountain shall have four push pads to activate the manual flow of water for the cooler. Basin shall be designed to eliminate splashing and standing water. Water saver bubbler to reduce waste water by 50% and shall have flexible guard and operate between 20 and 100 PSI. Cabinet finish shall be greystone on galvanized steel or sandstone powder coated or brushed stainless steel. Shall use R-134a refrigerant. Shall comply with ANSI 117.1 and ADA. Shall be listed by Underwriters Laboratories to US and Canadian standards. Shall comply with NSF/ANSI 61 and NSF/ANSI 372.



	PGF8ACSL	PGFACSL
<b>Features:</b>	<ul style="list-style-type: none"> <li>• Universal design: high right or high left</li> <li>• Built-in 100 micron strainer stops particles before they enter the waterway</li> <li>• Waterways are lead-free in materials &amp; construction</li> <li>• Flexible and one-piece water saver bubbler infused with silver-based antimicrobial additive</li> <li>• Stainless steel top and heavy duty galvanized steel frame</li> <li>• High efficiency cooling system</li> <li>• Four push pads</li> <li>• Includes integral self-scouring waste drain</li> <li>• External access to stream height adjustment on lower VersaCooler fountain</li> <li>• External access to thermostat with tool activated OFF position</li> <li>• Mechanical activation</li> </ul>	
<b>Filtration:</b>	VersaFilter III is Certified to NSF/ANSI 42 and 53 for lead, cyst, Particulate Class I, chlorine, taste and odor reduction to 4,750 gallons	
<b>Power:</b>	115 Volts, 60 Hz	
<b>Activation By:</b>	Manual Activation	
<b>Mounting Type:</b>	Wall Mounted	
<b>Chilling Option:</b>	8.0 gph*	Non-Refrigerated
<b>Full Load Amps</b>	5.0 amps	0 amps
<b>Rated Watts</b>	500	0
<b>Approx. Net Weight</b>	65 lbs	38 lbs
<b>Installation Location:</b>	Indoor	

### Installation

- Prior to rough-in consult with local, state and federal codes for proper mounting height
- Shipped with complete instructions and wall mounting bracket
- Removable side and front panels provide easy access for installation

### Finishes

- Standard: Greystone powder coat on galvanized steel
- Optional finishes: Sandstone powder coated paint; Stainless steel (at additional cost)

### Options

- Push handle glass fillers (029603-004)
- One piece chrome plated brass bubbler (036700-001)
- Cane apron (035174-001)

### Limited 5-Year Warranty

(Continental limits of the United States and Canada) Five years on the sealed refrigeration system and most component parts. Detailed warranty certificate enclosed with each water cooler; sample available upon request.

### Export Warranty

One year on components parts. Detailed warranty certificate enclosed with each drinking fountain; sample copy available upon request.

### Certifications/Compliance

- Certified to UL 399 and CAN/CSA C22.2 No.120 (electric water coolers only)
- Product Certified to NSF/ANSI Standard 61-G & 372 and conforms with the lead content requirements for "Lead Free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act
- These water coolers comply with the requirements of ADA (Americans with Disabilities Act) when properly installed



#### WARNING:

Cancer and Reproductive Harm  
www.P65Warnings.ca.gov

\*Industry standard rating condition at 90°F ambient, 80°F inlet water and 50°F drinking water temperature



Specifications subject to change without notice

# OASIS® BI-LEVEL VERSACOOLER® II FILTERED

