



We Know Water.

CONTACTLESS VERSACOOLER® II FILTERED

• PGF8ACT • PGFACT

Suggested Specification

Model PGF8ACT shall deliver 8.0 gph of 50°F water at 90°F ambient and 80°F inlet water per ASHRAE 18 testing. Model PGFACT is a non-refrigerated drinking fountain and delivers ambient water. Shall have VersaFilter III for taste, odor, lead and chlorine reduction. Shall include a contactless infrared sensor to activate the flow of water. Basin shall be designed to eliminate splashing and standing water. Water saver bubbler to reduce waste water by 50% and shall have flexible guard and operate between 20 and 100 PSI. Cabinet finish shall be greystone on galvanized steel or sandstone powder coated or brushed stainless steel. Shall use R-134a refrigerant. Shall comply with ANSI 117.1 and ADA. Shall be listed by Underwriters Laboratories to US and Canadian standards. Shall comply with NSF/ANSI 61 and NSF/ANSI 372.



	PGF8ACT	PGFACT
Features:	<ul style="list-style-type: none"> Built-in 100 micron strainer stops particles before they enter the waterway Waterways are lead-free in materials & construction Flexible and one-piece water saver bubbler infused with silver-based antimicrobial additive Stainless steel top and heavy duty galvanized steel frame High efficiency cooling system Includes integral self-scouring waste drain External access to stream height adjustment External access to thermostat with tool activated OFF position Contactless infrared sensor activation 	
Filtration:	VersaFilter III is Certified to NSF/ANSI 42 and 53 for lead, cyst, Particulate Class I, chlorine, taste and odor reduction to 4,750 gallons	
Power:	115 Volts, 60 Hz	
Activation By:	Contactless Sensor	
Mounting Type:	Wall Mounted	
Chilling Option:	8.0 gph	Non-Refrigerated
Full Load Amps:	5.0 amps	0.2 amps
Rated Watts:	500	11
Approx. Net Weight:	47 lbs	17 lbs
Installation Location:	Indoor	

Installation

- Prior to rough-in consult with local, state and federal codes for proper mounting height
- Shipped with complete instructions and wall mounting bracket
- Removable side and front panels provide easy access for installation

Finishes

- Standard cabinet finish: Greystone powder coated paint on galvanized steel
- Optional finishes: Sandstone powder coated paint; Stainless steel (at additional cost)

Options

- Push handle glass fillers (029603-004)
- One piece chrome plated brass bubbler (036700-001)

Limited 5-Year Warranty

(Continental limits of the United States and Canada)

Five years on the sealed refrigeration system and most component parts. Detailed warranty certificate enclosed with each water cooler; sample available upon request.

Export Warranty

One year on components parts. Detailed warranty certificate enclosed with each drinking fountain; sample copy available upon request.

Certifications/Compliance

- Certified to UL 399 and CAN/CSA C22.2 No.120 (electric water coolers only)
- Product Certified to NSF/ANSI Standard 61-G & 372 and conforms with the lead content requirements for "Lead Free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act.
- These water coolers comply with the requirements of ADA (Americans with Disabilities Act) when properly installed.



WARNING:

Cancer and Reproductive Harm
www.P65Warnings.ca.gov



*Industry standard rating condition at 90°F ambient, 80°F inlet water and 50°F drinking water temperature

Specifications subject to change without notice

OASIS® CONTACTLESS VERSACOOLER® II FILTERED

