



**We Know Water.**

**14 GAUGE VANDAL RESISTANT  
VERSACOOLER® II FILTERED**

- **PGVF8AC-14G**
- **PGVFAC-14G**

**Suggested Specification**

Model PGVF8AC-14G shall deliver 8.0 gph of 50°F water at 90°F ambient and 80°F inlet water per ASHRAE 18 testing. Model PGVFAC-14G is a non-refrigerated drinking fountain and delivers ambient water. Cabinet & basin shall be 14 gauge stainless steel, with a heavy duty galvanized frame, with galvanized steel screens to prevent objects from being inserted into ventilation panels or underside of unit. Unit shall include a single vandal resistant push button to activate the flow of water. Basin shall be designed to eliminate splashing and standing water. One-Piece low flow vandal resistant chrome plated solid construction bubbler keyed into place to prevent vandalism. Water saver bubbler to reduce waste water by 50% and shall have flexible guard and operate between 20 and 100 PSI. Shall use R-134a refrigerant. Shall comply with ANSI 117.1 and ADA. Shall be listed by Underwriters Laboratories to US and Canadian standards. Shall comply with NSF/ANSI 61 and NSF/ANSI 372.



	<b>PGVF8AC-14G</b>	<b>PGVFAC-14G</b>
<b>Features:</b>	<ul style="list-style-type: none"> <li>• Built-in 100 micron strainer stops particles before they enter the waterway</li> <li>• Waterways are lead-free in materials &amp; construction</li> <li>• 14 gauge stainless steel construction</li> <li>• Vandal resistant water saver bubbler</li> <li>• One-piece vandal resistant bubbler keyed into position</li> <li>• Vandal resistant fasteners</li> <li>• Galvanized steel louver and bottom screens</li> <li>• High efficiency cooling system</li> <li>• Vandal resistant mechanical front push button</li> <li>• Includes integral self-scouring waste drain</li> <li>• External access to stream height adjustment on lower VersaCooler fountain</li> <li>• External access to thermostat with tool activated OFF position</li> <li>• Mechanical activation</li> </ul>	
<b>Filtration:</b>	VersaFilter III is Certified to NSF/ANSI 42 and 53 for lead, cyst, Particulate Class I, chlorine, taste and odor reduction to 4,750 gallons	
<b>Power:</b>	115 Volts, 60 Hz	
<b>Activation By:</b>	Manual activation	
<b>Mounting Type:</b>	Wall Mounted	
<b>Chilling Option:</b>	8.0 gph	Non-Refrigerated
<b>Full Load Amps:</b>	5.0 amps	0
<b>Rated Watts:</b>	500	0
<b>Approx. Net Weight:</b>	54 lbs	24 lbs
<b>Installation Location:</b>	Indoor	

**Installation**

- Prior to rough-in consult with local, state and federal codes for proper mounting height
- Shipped with complete instructions and wall mounting bracket
- Removable side and front panels provide easy access for installation

**Finishes**

- Standard cabinet finish: Stainless steel

**Limited 5-Year Warranty**

(Continental limits of the United States and Canada) Five years on the sealed refrigeration system and most component parts. Detailed warranty certificate enclosed with each water cooler; sample available upon request.

**Export Warranty**

One year on components parts. Detailed warranty certificate enclosed with each drinking fountain; sample copy available upon request.

**Certifications/Compliance**

- Certified to UL 399 and CAN/CSA C22.2 No.120 (electric water coolers only)
- Product Certified to NSF/ANSI Standard 61-G & 372 and conforms with the lead content requirements for "Lead Free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act.
- These water coolers comply with the requirements of ADA (Americans with Disabilities Act) when properly installed.



**WARNING:**  
Cancer and Reproductive Harm  
[www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)



\*Industry standard rating condition at 90°F ambient, 80°F inlet water and 50°F drinking water temperature

Specifications subject to change without notice

# OASIS® 14 GAUGE VANDAL RESISTANT VERSACOOLER® II FILTERED

