



We Know Water.

CONTACTLESS QUASAR® VERSAFILLER® RETROFIT KIT

• PWEBQ

Suggested Specification

When retrofitted to either the PG8AC or P8AM, the PWEBQ bottle filler has independent contactless activation and laminar flow. VersaFiller alcove and cabinet shall be stainless steel. Key plastic components contain Freshield®, which utilizes a silver-based antimicrobial compound to protect the surfaces from discoloration, odors and degradation caused by the growth of micro-organisms and mildew.

QUASAR bottle filler shall have UV-C LED treatment at the dispense point, which disinfects the water while it is being dispensed. UV-C LED also cycles on periodically to keep the dispense point sanitized between dispenses.

When retrofitted to either the PG8AC or P8AM the VersaFiller models satisfy ANSI A117.1 and ADA requirements when properly installed. Units also meet guidelines for children's accessibility providing the floor to bubbler orifice height is 30 inches and proper clear floor space is provided for frontal approach. Shall be listed by Underwriters Laboratories to US and Canadian standards. Shall comply with NSF/ANSI 61 and NSF/ANSI 372.

Features:	<ul style="list-style-type: none"> • Contactless QUASAR with mercury-free UV-C LED treatment at the dispense point • Built-in 100 micron strainer stops particles before they enter the waterway • Waterways are lead-free in materials & construction • Heavy duty galvanized steel frame • Contactless activation bottle filler with programmable auto shut off • Ample space within the bottle filler cabinet to add filtration, including all OASIS filters • Access through the top of the bottle filler for clean and easy replacement of filters with Tilt 'N Tether • Built-in filter monitor and bottle counter • Logos permanently formed into the alcove and stainless steel wrapper • LED lighted alcove • Surface mount frame assembly
------------------	--

Filtration:	Utilizes existing filtration if applicable. Option to add filtration to top of bottle filler.
Power:	115 Volts, 60 Hz
Activation By:	Contactless Sensor
Mounting Type:	Wall Mounted
Chilling Option:	Utilizes existing refrigeration system if applicable
Full Load Amps:	0.40
Rated Watts	25
Approx. Net Weight:	17 lbs.
Installation Location:	Indoor



Installation

- Prior to rough-in consult with local, state, and federal codes for proper mounting height.
- Shipped with complete instructions and wall mounting brackets.

Finishes

- VersaFiller cabinet finish is stainless steel

Options

- Elkay Adapter Gasket 041533-001
- OASIS Versafilter III Kit 041253-001

Limited 1-Year Warranty

(Continental limits of the United States and Canada)

One year on components parts. Detailed warranty certificate enclosed with each water cooler; sample available upon request.

Export Warranty

One year on components parts. Detailed warranty certificate enclosed with each drinking fountain; sample copy available upon request.

Certifications/Compliance

- Certified to UL 399 and CAN/CSA C22.2 No.120 (electric water coolers only)
- Product Certified to NSF/ANSI Standard 61-G & 372 and conforms with the lead content requirements for "Lead Free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act
- These water coolers comply with the requirements of ADA (Americans with Disabilities Act) when properly installed



WARNING:

Cancer and Reproductive Harm
www.P65Warnings.ca.gov



Specifications subject to change without notice

The PWEBQ VersaFiller is designed to retrofit existing OASIS PG8AC and P8AM pressure cooler models. Units with optional glass fillers must have the glass filler disconnected and removed.

OASIS® PWEBQ CONTACTLESS QUASAR® VERSAFILLER® RETROFIT KIT

