



VersaFilter II

Filter cartridge for exceptional water filtration to reduce chlorine, taste, odor, lead, cysts, turbidity, dirt, rust and sediment, and to inhibit scale and corrosion*

*Claims for reduction of turbidity, dirt, rust, sediment, inhibition of scale and corrosion are based on manufacturer's testing.

Max Temp: 100°F (38°C)
Flow Rate: 1.67 gpm (6.321 Lpm)
Max Pressure: 125 psi (8.6 bar)
Capacity: 3,000 gals (11,355L)
Service Life: 12 months
Sediment: Down to 1 micron

For Commercial Use Only

[Replacement Cartridge](#)

Part # 041071-001



Certified by IAPMO R&T to NSF/ANSI Standards 42 & 53 for the reduction of: Chlorine, Taste, Odor, Cysts & Lead when used in the VersaFilter II.



Assembled
in the USA

Filter Install Date



WARNING:

Cancer and Reproductive Harm -
www.P65Warnings.ca.gov.

- NO ACTIVATION REQUIRED -

Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. System certified for cyst reduction may be used on disinfected waters that may contain filterable cysts. The system conforms to NSF/ANSI 53 for the specific performance claims as verified & substantiated by test data.

VersaFilter II by OASIS International
222 E. Campus View Blvd. Columbus, OH 43235
800.646.2747
www.oasiscoolers.com